


COMMUNITY SERVICE RAG QUILT INSTRUCTIONS

SUPPLIES: 108 8” Squares of flannel
54 6” squares of batting **or**
54 8” squares of Fleece —no batting needed


SANDWICHING: Flannel
Lay one 8” square wrong side up
Center 6” batting on top of the flannel
Place second 8” square right side up on top of batting.

QUILTING: Take the “flannel” sandwiched squares and sew an “X” from corner to corner.



Fabric, wrong side up

Lay another square of fabric, right side UP on top. You will now have 3 layers.



Stitch 2 lines of stitching, forming an X through all of the layers. Accuracy is not that important Use a good quality cotton thread.

Fleece squares do **not** need to be “quilted:

ASSEMBLE: Sew 6 “quilted” squares or square of fleece together to make a row.
Use 1” seams.
Make 9 rows.
Sew these 9 rows together to make the top.
Open seams at the intersections— for less bulk.
Keep all seams on the same side.
Sew 1” stitching around the whole outside edge of quilt.

SNIPPING: Take all of your seams and snip , but don’t cut through the stitching line.
Cut approximately 1/4” apart.

RAGGING: When all seams have been snipped, throw quilt into the washing machine and let it fray.
Tumble dry.
Note: You may want to go to a Laundromat to avoid clogging your machine, as there will be a lot of lint.

